

Kingsmen Hits 270 g/t AgEq Over 1.3 m in 1.5 km Step-Out on Parallel Structure at Las Coloradas

08.01.2026 | [Newsfile](#)

Vancouver, January 8, 2026 - [Kingsmen Resources Ltd.](#) (TSXV: KNG) (OTCQB: KNGRF) (FSE: TUY) ("Kingsmen" or the "Company") is pleased to report assays from three diamond drill holes at its Las Coloradas silver-gold project, Chihuahua, Mexico.

Key Results:

Drillhole LC-25-012 is the first hole testing the +1 km long Soledad II vein/structure. The hole was drilled approximately 1.5 km northwest of the Soledad discovery (which returned 1.45 m @ 1,028 g/t AgEq; reported September 24, 2025). Highlights include:

- 4.8 m @ 90 g/t AgEq (52.6 g/t Ag) from 56.7 m, including:
 - 1.3 m @ 270 g/t AgEq (143 g/t Ag & 0.72 g/t Au) from 56.7 m, including:
 - 0.8 m @ 360 g/t AgEq (220 g/t Ag & 0.223 g/t Au) from 57.2 m

Drillhole LC-25-009 is a 70 m step-out from discovery hole LC-25-008 (which returned 1.6 m @ 931 g/t AgEq and 1.28 g/t Au). Results confirm:

- Extension of LC-25-008 mineralization intersected, demonstrating continuity 70 m along strike
- Structure remains open and undrilled for 200 m to the south

President & CEO, Scott Emerson, commented: "These results demonstrate two critical factors for any discovery: grade and scale.

"On grade, hole LC-25-012 returned 270 g/t silver equivalent over 1.3 m in the first hole ever drilled on the Soledad II vein/structure (see Table 1) This follows our Soledad discovery intercept of 1,028 g/t silver equivalent over 1.45 m (see NR September 24, 2025). We are consistently intersecting high-grade mineralization across multiple structures.

"On scale, we have now confirmed significant mineralization in three separate structures-Soledad, Soledad II, and the newly identified No. 8-spanning a distance of 1.5 km northwest (see NR December 3, 2025). The Soledad II structure alone extends over one km at surface, where rock chip sampling has returned values up to 352 g/t silver and 2.42 g/t gold. We have drilled one hole on a km of prospective structure.

"The combination of high-grade intercepts and multiple parallel and sub-parallel mineralized vein/structures is what distinguishes a district-scale system from an isolated vein. Las Coloradas is demonstrating both."

WHY THIS MATTERS: GRADE + SCALE

These results confirm two key attributes of an emerging district: high-grade mineralization and the scale to host multiple targets. The vein/structure systems targeted by Kingsmen occur in a NW-trending area

approximately 2.5 km long and approximately 1 km wide. Kingsmen has now intersected significant mineralization in three separate structures. This is not a single vein-it is a mineralized system.

High-Grade Confirmed Across Three Structures

- Soledad - Discovery hole returned 1,028 g/t AgEq over 1.45 m
- Soledad II - First drill hole returns 270 g/t AgEq over 1.3 m (this release)
- No. 8 Structure - New discovery 1.6 m @ 931 g/t AgEq and 1.28 g/t Au

Soledad II: A 1.5 km Step-Out with Km-Scale Potential

Hole LC-25-012 is the first hole drilled on the Soledad II structure, located 1.5 km northwest of the original Soledad discovery. Surface sampling along the +1 km strike length has returned:

- 352 g/t Ag & 0.71 g/t Au
- 200 g/t Ag & 2.42 g/t Au

One hole has been drilled on a kilometre of prospective structure. Multiple targets remain untested.

Strike Continuity Confirmed at Rosario

Hole LC-25-009 extended mineralization 70 m along strike from discovery hole LC-25-008. The structure remains open and undrilled for 200 m to the south. Pathfinder geochemistry-including antimony, arsenic, bismuth, lead, and zinc-confirms the mineralizing system continues.

DETAILED DRILL DISCUSSION

Leona Target

Hole LC-25-012 is the first hole drilled on the +1 km-long Soledad II vein/structure. The hole was designed to test silver-gold mineralization beneath surface samples collected near the middle of the structure (Figures 1 and 2), which returned:

- 352 g/t Ag & 0.71 g/t Au
- 200 g/t Ag & 2.42 g/t Au

The hole intersected the mineralized structure at 56.7 m downhole, returning a 4.8 m wide zone dipping to the west (Figure 3, Table 1). This intersection confirms the potential of the Soledad II structure to host significant silver-gold mineralization, as first indicated by surface sampling. Anomalous silver and gold values extend along the full strike length of the structure, defining multiple targets for future drilling.

Table 1: LC-25-012 Assay Results

Hole ID	From (m)	To (m)	Width (m)	AgEq (g/t)	Au (g/t)	Ag (g/t)	Pb (%)	Zn (%)
LC-25-012	56.70	61.50	4.80	90	0.00	52	0.91	1.22
incl	56.70	58.00	1.30	270	0.72	143	2.45	3.42
incl	57.20	58.00	0.80	360	0.22	220	3.10	4.32
	138.30	138.55	0.25	209	0.14	157	0.61	1.91

The silver equivalent calculation formula is $\text{AgEq(g/t)} = ((\text{Ag grade (g/t)} \times (\text{Ag price per ounce}/31.10348)) \times \text{Ag}$

recovery) + (Pb grade (%) x (Pb price per tonne/100) x Pb recovery) + (Zn grade (%) x (Zn price per tonne/100) x Zn recovery) + (Au grade (g/t) x (Au price per ounce/31.10348) x Au recovery)) / (Ag price per ounce/31.10348 x Ag recovery). The prices used were US\$3675/oz gold, US\$2960/t zinc, US\$2003/t lead and US\$42/oz silver. Recoveries are estimated at 40% for gold, 91% for lead, 85% for zinc and 92% for silver based on published figures by [Kootenay Silver Inc.](https://kootenaysilver.com/news/kootenay/2024/kootenay-silver-announces-updated-mineral-resource-estimate-for-la-) for sulphide mineralization in the Cigarra deposit, Chihuahua, Mexico, a deposit with similar style mineralization (<https://kootenaysilver.com/news/kootenay/2024/kootenay-silver-announces-updated-mineral-resource-estimate-for-la->

Rosario Target

Holes LC-25-009 and LC-25-011 were collared 90 m northwest of LC-25-008 to test mineralization in the vicinity of the historic Rosario shaft (Figure 4).

Hole LC-25-009 targeted the mineralised structure intersected in LC-25-008, which returned 200 g/t AgEq & 0.28 g/t Au over 10.5 m, including 931 g/t AgEq & 1.28 g/t Au over 1.60 m. The hole intersected the structure at 118.0 m downhole, including a 0.65 m zone of anomalous gold and silver (118.15-118.8 m) with elevated pathfinder elements (antimony, arsenic, bismuth, lead, zinc; Table 2). This intersection is interpreted as an extension of the LC-25-008 mineralization, located approximately 70 m along strike to the southeast. The structure remains open and undrilled for 200 m south of LC-25-008.

Hole LC-25-011 intersected a broad alteration/structural zone from 90.73-157.8 m. Three zones of anomalous geochemistry were identified, characterised by low silver values, sporadic gold (up to 0.76 g/t over 0.6 m), and strong pathfinder signatures including antimony, arsenic, bismuth, and zinc (Table 2). The Rosario mine structure is interpreted between 131.75-137.65 m. The presence of pathfinder geochemistry, narrow silver-gold intersections, and associated alteration confirms the potential for mineralization in this area.

QAQC

The drill core (HQ size) is currently being geologically logged and sampled. The full drill core is sawn with a diamond blade rock saw. One half of the sawn drill core is bagged and tagged for analysis. The remaining half portion is returned to the drill core tray and stored. Bagged samples are securely stored prior to submission for analysis. Samples are being submitted to ALS Geochemistry-Chihuahua for multielement analysis following four-acid digestion (code ME-MS61), and gold by fire assay-AA (code Au-AA23). Quality assurance and quality control (QA/QC) is maintained by the systematic insertion of certified standard reference materials (CSRM), blanks and duplicates into the sample stream. Assay results will be announced following receipt, compilation and confirmation. ALS Geochemistry operates under a Global Geochemistry Quality Manual that complies with ISO/IEC 17025:2017.

About Las Coloradas

The Las Coloradas Project (8.5 km²) consolidates a historic mining district covering numerous silver-gold-lead-zinc-copper mines previously operated by ASARCO. Located in the Parral mining district of the Central Mexican Silver Belt, approximately 30 km southeast of Hidalgo de Parral.

Recent drilling has confirmed new zones of shallow, high-grade mineralization and highlighted potential for multiple parallel structures across a 4.5 km trend.

Qualified Person

Kieran Downes, Ph.D., P.Geo., a director of Kingsmen and Qualified Person as defined by National Instrument 43-101, has reviewed and approved the scientific and technical disclosure set out in this news release.

About Kingsmen Resources

Kingsmen Resources (TSXV: KNG) (OTCQB: KNGRF) (FSE: TUY) is a discovery-driven explorer focused on unlocking the potential of two 100%-owned precious-metal districts Las Coloradas and Almoloya located in the historic Parral region of Chihuahua, Mexico, one of the most productive silver belts in the world. Both projects cover past-producing high-grade silver and gold mines and lie directly on the structural corridors that host many of Mexico's most notable silver-gold deposits. Recent drilling at Las Coloradas has confirmed new zones of shallow, high-grade mineralization and highlighted the potential for multiple parallel structures across a 4.5 km trend. At Almoloya, historic drilling, extensive underground workings, and multiple vein systems point to strong potential for both vein-hosted and carbonate-replacement style mineralization. Kingsmen also owns a 1% NSR royalty on the La Trini claims within GoGold Resources' Los Ricos North project in Jalisco State, Mexico.

On behalf of the Board,
"Scott Emerson"

Scott Emerson, President & CEO
Phone: 604-685-9316
Email: se@kingsmenresources.com
Follow us on: LinkedIn, Instagram and X

Forward-Looking Statements:

Certain disclosure contained in this news release may constitute forward-looking information or forward-looking statements, within the meaning of Canadian securities laws. These statements may relate to this news release and other matters identified in the Company's public filings. In making the forward-looking statements the Company has applied certain factors and assumptions that are based on the Company's current beliefs as well as assumptions made by and information currently available to the Company. These statements address future events and conditions and, as such, involve known and unknown risks, uncertainties and other factors which may cause the actual results, performance or achievements to be materially different from any future results, performance or achievements expressed or implied by the statements. These risks and uncertainties include but are not limited to: the political environment in which the Company operates continuing to support the development and operation of mining projects; the threat associated with outbreaks of viruses and infectious diseases; risks related to negative publicity with respect to the Company or the mining industry in general; planned work programs; permitting; and community relations. Readers are cautioned not to place undue reliance on forward-looking statements. The Company does not intend, and expressly disclaims any intention or obligation to, update or revise any forward-looking statements whether as a result of new information, future events or otherwise, except as required by law.

Neither the TSXV nor its Regulation Services Provider (as that term is defined in the policies of the TSXV) accepts responsibility for the adequacy or accuracy of this release.

Figure 1 Leona silver samples & LC-25-012

To view an enhanced version of this graphic, please visit:
https://images.newsfilecorp.com/files/9640/279781_9af7e376944f49cc_004full.jpg

Figure 2 Leona gold samples & LC-25-012

To view an enhanced version of this graphic, please visit:
https://images.newsfilecorp.com/files/9640/279781_9af7e376944f49cc_005full.jpg

Figure 3 Leona Hole LC-25-012 section

To view an enhanced version of this graphic, please visit:
https://images.newsfilecorp.com/files/9640/279781_9af7e376944f49cc_006full.jpg

Figure 4 Rosario: LC-25-009 & LC-25-011

To view an enhanced version of this graphic, please visit:

https://images.newsfilecorp.com/files/9640/279781_9af7e376944f49cc_007full.jpg

Table 2:

HOLE ID	FROM	TO	WIDTH	Au ppm	Ag ppm	As ppm	Bi ppm	Cu ppm	Pb ppm	Sb ppm	Zn ppm
LC-25-009	114.15	114.60	0.45	0.005	1.18	214	2.74	33.8	69.6	3.42	115
LC-25-009	114.60	115.20	0.60	0.016	2.20	1340	2.90	21.6	248	3.91	2150
LC-25-009	115.20	115.70	0.50	0.041	2.91	4570	5.11	28.0	156	6.05	4220
LC-25-009	115.70	116.15	0.45	0.069	1.24	9620	3.12	19.5	42.2	9.84	3900
LC-25-009	116.15	116.65	0.50	0.014	0.63	1125	3.75	29.1	31.3	4.69	1200
LC-25-009	116.65	117.30	0.65	0.078	1.20	5900	5.02	33.0	45.4	14.50	3460
LC-25-009	117.30	117.60	0.30	0.024	2.55	808	6.03	57.0	111	10.15	8440
LC-25-009	117.60	118.15	0.55	0.192	3.40	10000	5.33	25.7	234	31.70	4980
LC-25-009	118.15	118.40	0.25	0.354	104.00	10000	237.00	47.0	5650	173.00	58700
LC-25-009	118.40	118.65	0.25	0.244	68.00	10000	99.70	374.0	4890	113.50	2380
LC-25-009	118.65	118.80	0.15	0.572	24.10	10000	77.20	27.1	1470	318.00	287
LC-25-009	118.80	119.25	0.45	0.012	2.06	455	2.70	10.5	158	12.80	328
LC-25-009	119.25	120.10	0.85	0.007	0.95	480	1.18	11.9	86.6	14.30	275
HOLE ID	FROM	TO	WIDTH	Au ppm	Ag ppm	As ppm	Bi ppm	Cu ppm	Pb ppm	Sb ppm	Zn ppm
LC-25-011	62.00	62.55	0.55	0.000	1.44	38.2	14.45	45.3	156	22.10	3150
LC-25-011	62.55	63.60	1.05	0.000	0.30	87.8	2.30	16.2	32	13.35	136
LC-25-011	63.60	64.00	0.40	0.000	0.27	99.3	2.07	13.9	21.1	6.84	152
LC-25-011	76.25	77.20	0.95	0.209	1.19	3330	1.74	16.2	15.1	57.60	71
LC-25-011	77.20	77.50	0.30	0.102	1.52	2910	1.88	12.8	17.2	112.50	126
LC-25-011	77.50	78.00	0.50	0.189	1.50	3200	2.58	30.1	29.6	146.50	1955
LC-25-011	78.00	79.00	1.00	0.087	3.91	1425	4.30	43.5	51.8	114.50	627
LC-25-011	79.00	80.00	1.00	0.000	2.52	200	5.99	35.8	58.3	103.50	2230
LC-25-011	80.00	81.00	1.00	0.059	5.33	1910	40.30	39.1	122	136.00	4630
LC-25-011	81.00	81.80	0.80	0.088	2.86	3820	6.45	31.3	35.1	207.00	931
LC-25-011	81.80	82.80	1.00	0.047	2.24	2510	2.97	31.7	29.3	119.00	2290
LC-25-011	82.80	83.70	0.90	0.059	2.39	4370	1.81	14.6	10.2	112.00	98
LC-25-011	83.70	83.95	0.25	0.338	10.80	10000	81.90	22.7	120.5	167.50	184
LC-25-011	83.95	84.75	0.80	0.051	1.60	1970	3.38	16.6	25.3	74.10	397
LC-25-011	86.00	86.25	0.25	0.000	1.02	59	15.25	36.9	50.8	10.70	3480
LC-25-011	118.00	119.00	1.00	0.000	0.67	72.9	2.82	36.7	30.1	1.35	159
LC-25-011	119.00	120.00	1.00	0.000	0.81	84.7	3.20	36.4	34.6	3.28	204
LC-25-011	120.00	120.60	0.60	0.008	2.60	659	7.68	122.0	79.4	8.31	19850
LC-25-011	120.60	121.55	0.95	0.000	0.53	113	2.07	35.5	24.7	2.57	176
LC-25-011	121.55	122.00	0.45	0.000	0.59	56.2	1.91	29.4	26.3	2.61	552
LC-25-011	122.00	123.00	1.00	0.007	1.01	663	3.16	55.5	52.3	2.89	3260
LC-25-011	123.00	123.50	0.50	0.033	5.34	7210	24.00	76.0	192	7.23	7730
LC-25-011	123.50	124.10	0.60	0.018	5.05	4070	44.20	75.6	157.5	5.96	9080
LC-25-011	124.10	124.80	0.70	0.029	4.58	9370	23.00	81.8	140.5	7.56	13050
LC-25-011	124.80	125.40	0.60	0.012	1.96	2540	14.30	60.9	67.7	3.32	5490
LC-25-011	125.40	126.00	0.60	0.758	19.90	10000	310.00	77.3	512	38.00	23600
LC-25-011	126.00	127.00	1.00	0.013	1.26	2260	4.09	55.9	51	2.93	3270
LC-25-011	127.00	128.00	1.00	0.008	0.97	1225	3.24	37.0	44.8	1.81	1425
LC-25-011	128.00	129.00	1.00	0.006	1.63	1465	3.28	33.3	77.9	2.24	1250
LC-25-011	129.00	130.00	1.00	0.000	0.93	291	2.16	21.5	66.1	2.33	979
LC-25-011	130.00	131.00	1.00	0.000	0.80	240	1.77	32.9	42.6	2.59	2210
LC-25-011	131.00	132.00	1.00	0.006	3.03	794	5.51	68.7	137	8.36	9140
LC-25-011	132.00	132.50	0.50	0.069	5.66	10000	4.83	7.3	861	17.00	9020
LC-25-011	132.50	133.00	0.50	0.016	1.38	1655	1.23	6.5	173.5	15.60	807
LC-25-011	133.00	133.55	0.55	0.139	2.23	10000	2.76	2.8	50.8	63.60	58
LC-25-011	133.55	133.90	0.35	0.519	56.80	10000	145.00	18.3	3880	698.00	8190

LC-25-011	133.90	134.50	0.60	0.017	3.86	1240	5.65	24.7	231	36.00	3380
LC-25-011	134.50	135.00	0.50	0.035	4.49	7060	6.28	20.9	217	58.90	301
LC-25-011	135.00	136.00	1.00	0.000	0.59	267	0.98	19.4	36.7	28.00	159
HOLE ID	FROM	TO	WIDTH	Au ppm	Ag ppm	As ppm	Bi ppm	Cu ppm	Pb ppm	Sb ppm	Zn ppm
LC-25-012	29.35	29.85	0.50	0.006	3.95	136	1.14	32.9	1060	49.90	1360
LC-25-012	29.85	30.05	0.20	0.396	44.80	10000	12.10	72.1	8130	252.00	19050
LC-25-012	30.05	31.00	0.95	0.005	2.44	239	0.19	39.9	486	60.30	1175
LC-25-012	31.00	32.00	1.00	0.000	0.19	59.2	0.11	10.5	15.1	9.48	186
LC-25-012	35.00	35.60	0.60	0.005	0.23	112	0.07	4.4	36.7	5.81	123
LC-25-012	50.00	50.40	0.40	0.050	12.20	10000	0.38	3.5	2210	82.90	882
LC-25-012	50.40	50.80	0.40	0.079	1.88	10000	0.34	1.6	295	71.70	139
LC-25-012	56.50	56.70	0.20	0.008	2.23	182.5	0.53	15.1	324	30.40	409
LC-25-012	56.70	57.20	0.50	1.510	18.95	10000	2.26	21.7	2430	457.00	2730
LC-25-012	57.20	58.00	0.80	0.223	220.00	10000	33.50	104.0	38400	313.00	54000
LC-25-012	58.00	59.00	1.00	0.034	16.10	3670	8.97	7.7	2340	19.20	2630
LC-25-012	59.00	60.00	1.00	0.013	10.75	709	1.37	8.2	2110	15.50	692
LC-25-012	60.00	61.00	1.00	0.047	24.70	5530	3.62	17.2	4830	41.10	3860
LC-25-012	61.00	61.50	0.50	0.027	27.70	3350	7.35	25.1	5120	36.40	14150
LC-25-012	69.50	70.05	0.55	0.011	0.89	73.3	0.16	32.3	81.9	51.20	145
LC-25-012	70.05	70.75	0.70	0.008	0.82	57.9	0.13	33.7	64.6	54.20	127
LC-25-012	70.75	71.15	0.40	0.000	0.80	20.6	0.07	18.9	99.1	41.30	65
LC-25-012	71.15	71.40	0.25	0.065	72.40	6950	2.70	59.9	15700	197.50	11650
LC-25-012	76.15	76.30	0.15	0.008	1.48	124	0.26	91.8	44.1	31.40	204
LC-25-012	138.00	138.30	0.30	0.041	8.26	6590	21.90	20.1	336	11.20	1630
LC-25-012	138.30	138.55	0.25	0.140	157.00	10000	380.00	33.4	6010	26.90	19150
LC-25-012	145.50	146.00	0.50	0.005	0.23	35.1	0.64	19.2	22.8	2.29	92
LC-25-012	146.00	146.30	0.30	0.005	2.29	322	3.83	18.6	204	1.56	277
LC-25-012	148.60	149.30	0.70	0.007	3.79	117	2.20	10.6	828	5.27	97
LC-25-012	151.35	151.80	0.45	0.000	0.28	34.5	0.44	9.1	39.3	1.93	48

True width cannot be determined at this time and reported widths are drilled intervals.

Table 3: Collar Information

Hole_ID	Easting	Northing	Elevation	Az	Dip	EOH
LC-25-009	464669	2964549	1660	220	-75	215.65
LC-25-011	464669	2964549	1660	250	-45	315.8
LC-25-012	463522	2964744	1640	45	-45	151.8

To view the source version of this press release, please visit <https://www.newsfilecorp.com/release/279781>

Dieser Artikel stammt von [Minenportal.de](https://www.minenportal.de)

Die URL für diesen Artikel lautet:

<https://www.minenportal.de/artikel/586759--Kingsmen-Hits-270-g-t-AgEq-Over-1.3-m-in-1.5-km-Step-Out-on-Parallel-Structure-at-Las-Coloradas.html>

Für den Inhalt des Beitrages ist allein der Autor verantwortlich bzw. die aufgeführte Quelle. Bild- oder Filmrechte liegen beim Autor/Quelle bzw. bei der vom ihm benannten Quelle. Bei Übersetzungen können Fehler nicht ausgeschlossen werden. Der vertretene Standpunkt eines Autors spiegelt generell nicht die Meinung des Webseiten-Betreibers wieder. Mittels der Veröffentlichung will dieser lediglich ein pluralistisches Meinungsbild darstellen. Direkte oder indirekte Aussagen in einem Beitrag stellen keinerlei Aufforderung zum Kauf-/Verkauf von Wertpapieren dar. Wir wehren uns gegen jede Form von Hass, Diskriminierung und Verletzung der Menschenwürde. Beachten Sie bitte auch unsere [AGB/Disclaimer!](#)

Die Reproduktion, Modifikation oder Verwendung der Inhalte ganz oder teilweise ohne schriftliche Genehmigung ist untersagt!

Alle Angaben ohne Gewähr! Copyright © by [Minenportal.de](https://www.minenportal.de) 2007-2026. Es gelten unsere [AGB](#) und [Datenschutzrichtlinien](#).